



Elfin IS

High Resolution Inkjet Printer



Controller and Printhead Separated

Separated type, suitable for different installation environment.



Online Edit

5 inch touch screen.



Cost Effective

Good for integration applications



Multiple Language Keyboard

Chinese, French, Turkish, Mexican, German, Korean, Spanish

Parameters

Specification	Controller: 151*93*32mm (H*W*D) / 5.9*3.7*1.3 inch
	Printhead: 175*52*33mm (H*W*D) / 6.9*2.0*1.3 inch
Language	Chinese, English, Korean, Japanese, French, German, Spanish, Portuguese and Russian
Resolution	50~600DPI
Counters	Can be set in Series No, Carton No, Pallet No, etc
Printable heights	1~12.7mm
Printing speed	0-60 m/min (300 DPI) 0-30 m/min (600 DPI)
Conveyor speed	Can be set, auto-calculated or use external synchronizer
Barcode	Code128, Code39, EAN8, EAN13, EAN128, UPCA, UPCE, INT25, ITF14, Code93, PDF417, QR, DataMatrix, GridMatrix, GS1RSS14, GS1RSS14Ex, GS1RSS14Limited, GS1RSS14Truncated, GS1EAN128, GS1RSS14Stacked, GS1RSS14StackedEX, GS1RSS14StackedOmni, GS1DM, Code128B, GS1QR
Date format	Production date, expiry date with several formats for option
Screen	5inch 800*480 resolution color LCD touch screen
Port	Ethernet: support PC software communication protocol SDK.
	USB2.0: Support U-Disk
	DB15: For external devices like photocell, synchronizer or alarm kit.
Ink management	Identify ink type automatically and adopt the best printing parameters
	Original HP ink cartridge guaranteed Automatic measuring system for ink consumption
Installation	Standard side printing, down printing bracket and anti-shock bracket, users can install according to their needs
Power supply	AC 100V-240V/50-60HZ, 30W (Dedicated AC adaptor)
Certificate	CE, FCC

Product photos

